


โปรแกรมการคำนวณคาร์บอนฟุตพริ้นท์พัฒนาโดย องค์การบริหารจัดการก๊าซเรือนกระจก (องค์การมหาชน) หรือ อบก.

เดือน มกราคม - ธันวาคม ประจำปี 2567


ขอบเขตการดำเนินงาน	รายการ	EF	หน่วย	หน่วยการเก็บข้อมูล	เดือน มกราคม - ธันวาคม ประจำปี 2567																				หน่วย					
					ม.ค.		ก.พ.		มี.ค.		เม.ย.		พ.ค.		มิ.ย.		ก.ค.		ส.ค.		ก.ย.		ต.ค.			พ.ย.		ธ.ค.		รวม
					ปริมาณ	CF	ปริมาณ	CF	ปริมาณ	CF	ปริมาณ	CF	ปริมาณ	CF	ปริมาณ	CF	ปริมาณ	CF	ปริมาณ	CF	ปริมาณ	CF	ปริมาณ	CF		ปริมาณ	CF			
Scope 1 (ประเภท 1)	1. การเผาไหม้แบบอยู่กับที่ (Stationary Combustion)																													
	การใช้น้ำมันสำหรับงานอาคาร																													
	Diesel (Generator)	2.7078	kg CO ₂ e/ลิตร	ลิตร	0	0.00	0	0.00	0	0.00	0.0000	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	kgCO ₂ e		
	Diesel (Fire pump)	2.7078	kg CO ₂ e/ลิตร	ลิตร	0	0.00	0	0.00	0	0.00	0.0000	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	kgCO ₂ e		
	2. การเผาไหม้แบบเคลื่อนที่ (Mobile Combustion)				0	0.00	0	0.00	0	0.00	0.0000	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	kgCO ₂ e		
Scope 2 (ประเภท 2)	การใช้พลังงานไฟฟ้า	0.4999	kg CO ₂ e/kWh	KWh	6,194.53	3,096.65	6,070.71	3,034.75	-	-	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	6131.39	kgCO ₂ e		
	การให้กระดาษ A4 และ A3 (สีขาว)	2.1020	kg CO ₂ e/kg	kg	425.00	893.35	382.50	761.98	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1655.33	kgCO ₂ e		
	น้ำประปา-การประปานครหลวง	0.7948	kg CO ₂ e/m ³	m ³	44.72	35.54	45.64	36.27	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	71.82	kgCO ₂ e		
Scope 3 (ประเภท 3)	ขยะของเสีย (ฝังกลบ)	2.3200	kg CO ₂ e/kg	kg	124.00	287.68	76.00	176.32	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	464.00	kgCO ₂ e		
	รวม				7,295.81	6,671.17	6,906.43	5,851.88	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	12,523.05	kgCO ₂ e	
	ปริมาณการปล่อยก๊าซเรือนกระจก		ICO ₂ e		7.30	6.67	6.91	5.85	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	12.52	tCO ₂ e	
จำนวนคนแต่ละเดือน		ICO ₂ e		145	145	145	145	145	145	150	150	150	150	150	150	150	150	150	150	150	150	150	150	150	150	150	145	tCO ₂ e		
ปริมาณการปล่อยก๊าซเรือนกระจกต่อคน		ICO ₂ e		0.050	0.046	0.048	0.040	0.00	0.000	0.00	0.000	0.00	0.000	0.00	0.000	0.00	0.000	0.00	0.000	0.00	0.000	0.00	0.000	0.00	0.000	0.00	0.09	tCO ₂ e		

หมายเหตุ: ค่าการปล่อยก๊าซเรือนกระจก (Emission Factor) รวบรวมมาจากข้อมูลทุติยภูมิ สำหรับการประเมินคาร์บอนฟุตพริ้นท์ขององค์กร update (7-12-2565)

ปริมาณการปล่อยก๊าซเรือนกระจก เดือน มกราคม - ธันวาคม 2567 (กิโลกรัมคาร์บอนไดออกไซด์เทียบเท่า : kgCO₂e)



ปริมาณก๊าซเรือนกระจก (tCO₂e / kgCO₂e)



การคำนวณ CH4 จาก Septic tank

ข้อมูล	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov
จำนวนวันเปิดบริการ/ทำการ	22	20	21	19	20	19	21	21	21	21	21
จำนวนพนักงานองค์กร	145	145	0	0	0	0	0	0	0	0	0
CH4 Emission	38.28	34.80	-	-	-	-	-	-	-	-	-

หมายเหตุ - การปล่อยก๊าซเรือนกระจกจากระบบ septic tank คำนวณเฉพาะประชากรพนักงานขององค์กรเท่านั้น

หมายเหตุ

treatment/discharge) เนื่องจากมีระบบเดียว

group in inventory year) เนื่องจากสัดส่วน

$$EF = 0.6 \text{ kg CH}_4 / \text{kg BOD} \times 0.5$$

$$= 0.3 \text{ kg CH}_4 / \text{kg BOD}$$

EQUATION 6.2
CH₄ EMISSION FACTOR FOR EACH DOMESTIC WASTEWATER TREATMENT/DISCHARGE PATHWAY OR SYSTEM

$$EF_j = B_o \cdot MCF_j$$

Where:

- EF_j = emission factor, kg CH₄/kg BOD
- j = each treatment/discharge pathway or system
- B_o = maximum CH₄ producing capacity, kg CH₄/kg BOD
- MCF_j = methane correction factor (fraction), See Table 6.3.

EQUATION 6.3
TOTAL ORGANICALLY DEGRADABLE MATERIAL IN DOMESTIC WASTEWATER

$$TOW = P \cdot BOD \cdot 0.001 \cdot f \cdot 365$$

Where:

- TOW = total organics in wastewater in inventory year, kg BOD/yr
- P = country population in inventory year, (person)

EQUATION 6.1
TOTAL CH₄ EMISSIONS FROM DOMESTIC WASTEWATER

$$CH_4 \text{ Emissions} = \left[\sum_{i,j} (U_i \cdot T_{i,j} \cdot EF_j) \right] (TOW - S) - R$$

TABLE 6.4
ESTIMATED BOD₅ VALUES IN DOMESTIC WASTEWATER FOR SELECTED REGIONS AND

Country/Region	BOD ₅ (g/person/day)	Range
Africa	37	35 – 45
Egypt	34	27 – 41
Asia, Middle East, Latin America	40	35 – 45
India	34	27 – 41
West Bank and Gaza Strip (Palestine)	50	32 – 68
Japan	42	40 – 45
Brazil	50	45 – 55
Canada, Europe, Russia, Oceania	60	50 – 70
Denmark	62	55 – 68
Germany	62	55 – 68
Greece	57	55 – 60
Italy	60	49 – 60
Sweden	75	68 – 82
Turkey	38	27 – 50
United States	85	50 – 120

Note: These values are based on an assessment of the literature. Please use national values, if available.

Reference:

- Doorn and Liles (1999).
- Feachem *et al.* (1983).
- Masotti (1996).
- Metcalf and Eddy (2003).

	kg	2.93	1	1	0.3	290	40	0.001	244
CH4 Emission									

#####